

Dünyanın En sessiz , yüksek Hızlı Dome MPEG4 IP Camerası

MPEG-4

iCanView 270

Dış Mekan

Yeni

Özellikler



i-NVR
yazılımı



1 kanal Active-X görüntüleyici
Web browser eklentisi

- World Most Silent Speed Dome IP Camera (Outdoor Type)
- 1/4 " Sony Ex -view CCD 10x optic, 10x digital, total 100x zoom.
- Filter Changeable Type Day & Night
- IP66 water-resistant
- State-of-the-art CPU, Codec & Embedded SW
- Superior video compression – MPEG-4
- Max 30 frames/sec @ D1 resolution
- Full D1 Resolution with De-interlaced filter
- Bi-directional audio communication- Up(ADPCM), Down(PCM)
- Synchronized 1CH audio & video data transmission
- Intelligent Bit Rate Control for flexible network deployment
- Enhanced Image Quality
- MPEG4+JPEG Dual Stream for mobile WAP network
- Embedded Streaming Server and Embedded Web Server
- Motion detected and event triggered alarm processing
- Easy recording and playback on client PC
- Sensor triggered (2) alarm input & (1) relay output
- Wide range of network protocols supported
- RoHS Compliant Product
- System time management
 - RTC and with Time Server synchronization
- Security support
 - User authentication
 - Encrypted streaming data for additional security (selectable)
- Option : Various CCTV Camera selectable
- View and Recording/Control Software & Solution
 - i-NVR <16CH Monitoring/Recording/Control S/W>
 - Web Viewer <Active-X based viewer software>
 - NVR Pro <Over 64CH Monitoring/Recording/Control S/W>

iCanView 240

Dış Mekan

Specifications



i-NVR(bütünleşmiş
Network Video
kaydedici)



1 Kanal Active-X
Görüntüleyici

- **Real Audio & Video Coding based on Int'l Standard**
 - ... MPEG-4 (36K bps -1.5 Mbps) for video, ADPCM for audio
- **Bi-directional Audio Communication**
- **Embedded Streaming Server**
 - ... Transmits synchronized audio & video data in a single channel simultaneously
- **Video Resolution & Frame Rate**
 - ... NTSC : 720x480(D1), 320x240(QVGA),176x144(QCIF), Max. 30frames/sec
 - ... PAL/SECAM : 704x576,704x288, 352x288(CIF),176x144(QCIF) , Max. 25frames/sec
- **Display mode on client PC viewer**
 - ... 1Ch Full Screen, 1Ch 640 x 480, 4Ch 320x240, 9/16/Ch 160x120
- **Hardware**
 - ... 32bit RISC embedded processor
 - ... Flash memory : 8M Bytes ... SDRAM : 32M Bytes ... OS : RTOS
- **Alarms and I/O Control**
 - ... Alarms 1. Motion detected alarm
 - 2. Sensor triggered one alarm input & one relay output
 - ... Event triggered transmission to remote server (email)
- **Remote P/T/Z Control**
- **Multi-channel viewing/recording/controlling S/W(i-NVR)–free of charge**
 - ... Capability to save and retrieve audio/video stream & still image
 - ... Easy brightness/contrast control
 - ... 16 Ch Video/Audio display (i-NVR), Active-X based viewer program(1CH)
 - ... Automatic download and installation
- **Multiple Access Network Provided**
 - ... Ethernet(100Base-T), ADSL Modem, Cable Modem
- **Supported Protocols**
 - ... TCP/IP, ARP, ICMP, HTTP, SMTP, FTP, DHCP, RTP, RTSP, SDP, PPPoE
- **User Registration and Password Protection Capability**
- **Operating Temperature**
 - ... -0°C ~ 50°C (14°F ~122°F)
- **Power**
 - 23W Max
 - Adaptor :AC24V 1.5A, 36VA